

HOSHIZAKI





Series

KM900M_H
Item # 13033 05/04

KM-900M_H SERIES





KM-900MAH
Air-Cooled
KM-900MWH
Water-Cooled
KM-900MRH
Air-Cooled Remote 1 Phase
KM-900MRH3
Air-Cooled Remote 3 Phase



**KM-900MAH Cuber
Shown on Optional
B-900 Bin**

ICEMAKER DIMENSION	
Width x Depth x Height	
KM-900M_H	
30 x 27 ³ / ₈ x 37 ⁷ / ₁₆ "	
DIMENSION BYBIN SIZE	
Width x Depth x Height	
B-500	30 x 32 ¹ / ₂ x 83 ⁷ / ₁₆ "
B-700	44 x 32 ¹ / ₂ x 83 ⁷ / ₁₆ "
B-800	48 x 32 ¹ / ₂ x 83 ⁷ / ₁₆ "
B-900	52 x 32 ¹ / ₂ x 83 ⁷ / ₁₆ "

- Durable stainless steel exterior
- CycleSaver® design 
- EverCheck® alert system 
- Up to 846 lbs. of ice production per 24 hours
- Individual crescent cube
- Stainless steel evaporator
- Removable air filters (Air-cooled model only)



© HOSHIZAKI AMERICA, INC.

618 Hwy. 74 S., Peachtree City, GA30269

1-800-438-6087

FAX 1-800-345-1325

TEL 770-487-2331

www.hoshizaki.com




Reliability is a beautiful thing™

MODULAR CRESCENT ICE CUBER

MODULAR CRESCENT ICE CUBER

- KM-900MAH** (AIR-COOLED)
- KM-900MWH** (WATER-COOLED)
- KM-900MRH** (AIR-COOLED REMOTE 1Ø)
- KM-900MRH3** (AIR-COOLED REMOTE 3Ø)



■ Up to 846 lbs. of ice production per 24 hours



WARRANTY THREEYEAR - Parts & Labor on entire machine. FIVEYEAR - Parts & Labor on : Evaporator FIVEYEAR - Parts on: Compressor, Air-Cooled Condenser Coil.	STAINLESS STEEL	SERVICE Panels easily removed and all components accessible for service. Removable/cleanable air filters.	Warranty valid in United States, Canada, Puerto Rico, & U.S. Territories. Contact Factory for Warranty in other Countries.
	INTERNAL EVAPORATOR		
	R-404 REFRIGERANT		

STORAGE BINS

B-500 - 500 lb. Application Capacity (360 lb. ARI-Rated Capacity Bin)
 B-700 - 700 lb. Application Capacity (550 lb. ARI-Rated Capacity Bin)
 B-800 - 800 lb. Application Capacity (600 lb. ARI-Rated Capacity Bin)
 B-900 - 900 lb. Application Capacity (660 lb. ARI-Rated Capacity Bin)
 B-1200 - 1200 lb. Application Capacity
 B-1500 - 1500 lb. Application Capacity

ELECTRICAL & PLUMBING
 208-230/60/1
 (3 wire with dedicated neutral for 115V)
 20 amp Max Fuse/HACR Breaker Size
 Air-Cooled Units
 15 amp Max Fuse/HACR Breaker Size
 Water-Cooled Units
 208-230/60/3 - 20 amp Max
 Fuse/HACR Breaker Size
 1/2" OD copper or equivalent independent
 potable water supply
 3/4" independent drain connection

OPERATING LIMITS
 Ambient Temp Range 45 - 100°F
 Water Temp Range 45 - 90°F
 Voltage Range 187-253V
 Water Pressure 10 - 113 psig

SPECIFICATIONS

Model Number	Condenser	Amperage	Min. Circuit Ampacity	Shipping Weight
KM-900MAH	Air-Cooled	11.0	20	282 lbs.
KM-900MWH	Water-Cooled	10.2	15	282 lbs.
KM-900MRH	A-C Remote	12.5	20	282 lbs.
KM-900MRH3	A-C Remote	6.5	20	282 lbs.

AIR - COOLED

Water Temp ° F.	50°	70°	90°
Air Temp ° F.			
70°	838	809	759
80°	816	770	715
90°	809	738	684

WATER - COOLED

Water Temp ° F.	50°	70°	90°
Air Temp ° F.			
70°	846	833	787
80°	836	815	754
90°	833	801	745

AIR - COOLED REMOTE 1 PHASE

Water Temp ° F.	50°	70°	90°
Air Temp ° F.			
70°	835	826	786
80°	824	802	758
90°	821	786	745

AIR - COOLED REMOTE 3 PHASE

Water Temp ° F.	50°	70°	90°
Air Temp ° F.			
70°	842	832	784
80°	835	820	753
90°	832	809	749

UTILITY CONSUMPTION

Model Number	Ice Production Per Cycle	KWH per 100 LBS.	Potable Water Gal. per 100 lbs.	Condenser Water Gal. per 100 lbs.
KM-900MAH	14.3 Lbs. / 720 Cubes	6.4	32.1	NA
KM-900MWH	14.3	5.1	32.3	100
KM-900MRH	14.3	6.2	31.7	NA
KM-900MRH3	14.3	6.2	32.1	NA

