

# HOSHIZAKI

## Series


KML-250/350M\_H  
Item # 13126 503

**KML-250/350M\_H SERIES**




**KML-250MAH Cuber  
Shown on Optional  
B-500 Bin**

**KML-250MAH**  
Air-Cooled  
**KML-250MWH**  
Water-Cooled  
**KML-350MAH**  
Air-Cooled  
**KML-350MWH**  
Water-Cooled



**B-250**





**B-500**



**DB-200**

|   |
|---|
| <b>ICEMAKER<br/>DIMENSION</b><br>Width x Depth x Height<br><b>KML-250/350M_H</b><br>30 x 27 <sup>3/8</sup> x 22   |
| <b>DIMENSION<br/>BYBIN SIZE</b><br>Width x Depth x Height<br><b>B-250</b><br>30 x 32 <sup>1/2</sup> x 55 <sup>3/8</sup><br><b>B-500</b><br>30 x 32 <sup>1/2</sup> x 68<br><b>DB-200</b><br>30 x 30 x 75 |

- Durable stainless steel exterior
- CycleSaver™ design 
- EverCheck™ alert system 
- Individual crescent cube eliminates splashing and displacement is excellent
- Stainless steel evaporator
- Removable air filters
- Lower height for restricted areas (stairwells, low ceilings)

**KML-250M\_H**

- Up to 314 lbs. of ice production per 24 hours

**KML-350M\_H**

- Up to 354 lbs. of ice production per 24 hours

© HOSHIZAKI AMERICA, INC.

618 Hwy. 74 S., Peachtree City, GA30269

TEL1-800-438-6087



Reliability is a beautiful thing®


FAX 1-800-345-1325

www.hoshizaki.com

**LOW PROFILE MODULAR CRESCENT CUBER**

**LOW PROFILE MODULAR CRESCENT CUBER**

KML-250MAH (AIR-COOLED)  
 KML-250MWH (WATER-COOLED)  
 KML-350MAH (AIR-COOLED)  
 KML-350MWH (WATER-COOLED)



- Up to 314 & 354 lbs. of ice production per 24 hours
- Individual unique crescent cube eliminates splashing and displacement is excellent



**WARRANTY**

**THREEYEAR** - Parts & Labor on entire machine.  
**FIVEYEAR** - Parts & Labor on: Evaporator  
**FIVEYEAR** - Parts on: Compressor; Air-Cooled Condenser.

**STAINLESS STEEL  
 INTERNAL EVAPORATOR**

**R-404 REFRIGERANT**

**SERVICE**

Panels easily removed and all components accessible for service.  
 Removable/cleanable air filters.

Warranty valid in United States, Canada, Puerto Rico, & U.S. Territories. Contact Factory for Warranty in other Countries.

**STORAGE BINS**

B-250 - 250 lb. Application Capacity (230 lb. ARI-Rated Capacity Bin)  
 B-500 - 500 lb. Application Capacity (360 lb. ARI-Rated Capacity Bin)  
 B-700 - 700 lb. Application Capacity (550 lb. ARI-Rated Capacity Bin)  
 B-800 - 800 lb. Application Capacity (600 lb. ARI-Rated Capacity Bin)  
 B-900 - 900 lb. Application Capacity (660 lb. ARI-Rated Capacity Bin)  
 B-1200 - 1200 lb. Application Capacity  
 B-1500 - 1500 lb. Application Capacity

**OPERATING LIMITS**

Ambient Temp Range 45 - 100°F  
 Water Temp Range 45 - 90°F  
 Voltage Range 104 - 127V  
 Water Pressure 10 - 113 psig

**ELECTRICAL & PLUMBING**

115/60/1  
 20 amp Max Fuse/HACR Breaker Size  
 1/2" OD copper or equivalent independent potable water supply  
 3/4" independent drain connection

**AIR - COOLED KML-250 / KML-350**

| Water Temp ° F. | 50°       | 70°       | 90°       |
|-----------------|-----------|-----------|-----------|
| Air Temp ° F.   |           |           |           |
| 70°             | 307 / 350 | 284 / 336 | 267 / 309 |
| 80°             | 289 / 339 | 253 / 317 | 245 / 287 |
| 90°             | 284 / 336 | 227 / 301 | 215 / 272 |

**WATER - COOLED KML-250 / KML-350**

| Water Temp ° F. | 50°       | 70°       | 90°       |
|-----------------|-----------|-----------|-----------|
| Air Temp ° F.   |           |           |           |
| 70°             | 314 / 354 | 304 / 345 | 290 / 330 |
| 80°             | 306 / 347 | 290 / 334 | 277 / 316 |
| 90°             | 304 / 345 | 279 / 324 | 265 / 307 |

**UTILITY CONSUMPTION**

| Model Number | Ice Production Per Cycle |       | KWH per 100 lbs. | Potable* Water Gallons per 100 lbs. | Condenser* Water Gallons per 100 lbs. |
|--------------|--------------------------|-------|------------------|-------------------------------------|---------------------------------------|
|              | Lbs.                     | Cubes |                  |                                     |                                       |
| KML-250MAH   | 6.6                      | 360   | 8.4              | 33.2                                | NA                                    |
| KML-250MWH   | 6.6                      | 360   | 6.5              | 37.2                                | 146                                   |
| KML-350MAH   | 7.3                      | 360   | 7.6              | 25.5                                | NA                                    |
| KML-350MWH   | 7.3                      | 360   | 6.6              | 26.9                                | 124                                   |

**SPECIFICATIONS**

| Model Number | Condenser    | Amperage | Min. Circuit Ampacity | Shipping Weight |
|--------------|--------------|----------|-----------------------|-----------------|
| KML-250MAH   | Air-Cooled   | 8.2      | 20                    | 180 lbs.        |
| KML-250MWH   | Water-Cooled | 7.5      | 20                    | 180 lbs.        |
| KML-350MAH   | Air-Cooled   | 11       | 20                    | 180 lbs.        |
| KML-350MWH   | Water-Cooled | 10.5     | 20                    | 180 lbs.        |

\*At 90° Air / 70° Water

We reserve the right to change specifications without notice.

